



From spray paint graffiti to smash-and-grab robbers, property owners and managers are in a constant battle to protect their glass and property. Johnson Window Films' **Defendor** clear anti-graffiti films provide the perfect solution. With a unique polyester construction bonded with special adhesives, Defendor provides protection for glass, metal and non-porous surfaces.

AG04

Defendor is optically clear and undetectable to the naked eye, so it won't hamper views. Defendor 04 offers 16% in heat reduction, while still allowing 87% of visible light.

Available in two thicknesses-4 mil and 6 mil – this product allows dealers an option depending on the desired level of protection. The unique 2 ply construction of the AG04 makes for an easier installation and eventual removal.

The combined rejection properties of this product result in 47% slowing of interior fading.

- Protected with CST[™] scratch-resistant hardcoat to ensure long lasting durability, protection and clarity.
- Blocks 99% of harmful UV rays minimizing UV health risks to skin and eyes.
- Comprehensive manufacturer's warranty available.





The Skin Cancer Foundation recommends ohnson Window Films products as effective UV protectants









ABOUT WINDOW FILM

Window film acts as a "sunscreen" to block harmful UV rays, as it regulates the levels of heat and light passing through the glass. The amount of heat and light rejected is dependent upon the type of window film selected.

When applying our window film to glass, nearly 80% of solar energy is blocked. This creates a solar energy barrier by absorbing or reflecting a percentage of the solar energy being passed through the glass.



Window film does not completely eliminate interior fading, but it offers a reduction in the causes of fading. It reduces UV light, solar heat and visible light by blocking percentages of the causes. However, window film has no effect on items like dye fastness, age of fabrics and humidity, which is encompassed in the misc amount of 10% seen in the diagram.



Solar specifications represent film mounted to 1/8 inch (3mm) clear glass. Tests, equipment and methods are in accordance with ASTM, ANSI and NFRC standards. Calculations performed using Lawrence Berkeley Laboratory's Optics / Window 6. Values expressed hereof are typical and provided for comparative purposes only.



##