

T.T.D. Application Tape

SPECIFICATIONS

Composition	Average Thickness	Carrier	Available in 4 versions	Certifications
adhesive PES	75-80* microns	Silicon paper	TTD Advanced (low tack) TTD Easy (medium tack) TTD Evolution (high tack) TTD Special (high tack)*	REACH n° 1907/2006/EU

TO BE USED WITH

Product	TTD Advanced (low tack)	TTD Easy (medium tack)	TTD Evolution (high tack)	TTD Special (high tack)
COLORPRINT®	OK	OK	OK	
COLORPRINT® EXTRA	OK	OK	OK	
COLORPRINT® NEW M		OK	OK	
COLORPRINT® PU		OK	OK	
COLORPRINT® PU EXTRA		OK	OK	
EASY SUBLI®				OK
HI-5 PRINT		OK	OK	
SOFT PRINT COLOR		OK		
SUBLITHIN MATT LT		OK	OK	

NOTE: We highly recommend to perform a test before launching a production.

APPLICATION INSTRUCTIONS

- Remove the protective paper from T.T.D.
- Apply the T.T.D. onto the printed logo, manually or using a laminator, avoiding air bubbles
- Remove the backing of the digital, printed media
- Heat apply following the instructions of the digital media
- Remove T.T.D. according the given instructions for the product in use..

This document can be subject to variations. Updated versions are available on www.siser.com
For further information, please contact our sales office: info@siser.it



Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it
www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246



Management System
ISO 9001:2015
ISO 14001:2015

